


Installation Instructions for eDriveTC v3.25

1. Download **Autoloader_eDrive v3_25** from the Outback Guidance website and save it to your computer.
2. Unzip the **Autoloader_eDrive_3_25** file by double clicking the file.
3. Power on the eDriveTC and connect the eDriveTC to the computer with a serial cable.
4. Choose the PC COM port of the serial cable.
5. Click **Load**. The Autoloader will display a progress bar. **Do not** stop or interrupt the update during this time.
6. When the install is complete and the STX screen indicates it is OK to do so, remove the USB drive and reboot the eDriveTC.
7. On the STX terminal, verify the new software version in the Firmware Version field as shown at right.



Installation Instructions for Outback STX v1.0

1. Download **STX 1.0.3.1.12133** from the Outback Guidance website and save it to your computer.
2. Unzip the software by double clicking the **STX-1.0.3.1.12133** file.
3. Copy the **STX_Update** file to the USB drive provided in your STX kit. Ensure the file is named "STX_Update".
4. Verify the Outback STX terminal is powered off. Insert the USB drive in the USB port on the STX terminal. Power on the Outback STX terminal. After less than a minute, an install screen will appear as shown in step 5.
5. Press the **Press to Begin Installation** button (first screen at right).
6. Press the **Press to Perform Firmware Update** button (second screen at right).



WARNING: The Press to Clear All Data and Reinstall Firmware button will erase all jobs, profiles, templates, and calibrations on the terminal and reset all values to factory defaults.

Estimated Install Time: <10 min

7. When the install is complete and the message at right appears, remove the USB drive and reboot the terminal.



8. To verify the new software version, on the STX terminal press the **Tools** button. The version will be displayed in the Application field under the **System** tab.

